

GreenGuard® Fanfold Underlayment INSTALLATION GUIDELINES



Verify that substrate is flat, dry, and free of foreign material that will damage the GreenGuard® Fanfold Underlayment. Beginning of installation means installer accepts the existing conditions.

- A. Install GreenGuard Fanfold Underlayments directly over old siding using galvanized or aluminum roofing nails, with nails spaced about 2 feet apart. If the existing siding is damaged, remove it and install GreenGuard Fanfold Underlayment directly to the substrate.
- B. Install the new siding material over GreenGuard Fanfold Underlayment in accordance with the siding manufacturer's installation instructions.
- C. Care should be taken when installing GreenGuard Fanfold Underlayment under siding materials. These products must be adequately fastened so that the entire board lays completely flat against the existing siding material or sheathing. Avoid overdriving fasteners, since this will crush the insulation, resulting in a wavy appearance of the finished exterior wall. Additional R-value can be obtained by installing GreenGuard FP38 or XFP14 using 1/2" wood furring strips between the existing siding and the reflective surface of the products.

For the most current product and code compliance information, go to www.green-guard.com

Warning: Foam plastic insulation will ignite if exposed to fire of sufficient heat and intensity. Protect foam insulation from exposure to open flame or other ignition sources during shipment, storage, and installation.

Storage and Handling: When stored outdoors, all materials should be protected from exposure to direct sunlight using an opaque light-colored tarp or the original packaging. Material that has been unwrapped should be carefully rewrapped.

Pactiv Building Products believes the information and recommendations herein to be accurate and reliable. However, since use conditions are not within its control, Pactiv does not guarantee results from use of such products or other information herein and disclaims all liability from any resulting damage or loss. NO WARRANTY, EXPRESS OR IMPLIED, IS GIVEN AS TO THE MERCHANTABILITY, FITNESS FOR PARTICULAR PURPOSE, OR OTHERWISE WITH RESPECT TO THE PRODUCTS REFERRED TO.

GreenGuard is a registered trademark of Pactiv Building Products © 2004 Pactiv Building Products.